

## PROVEN PROTECTION FOR YOUR VEHICLE AND THE PLANET

Safety-Kleen Systems, Inc. www.safety-kleen.com, www.ecopoweroil.com

## **HEAVY-DUTY DIESEL XHD-7 10W-30**

**EcoPower® Heavy-Duty Diesel XHD-7 10W-30 Motor Oil** is specifically engineered to meet the latest requirements for EGR/EPF engines. Meets or exceeds API Service CJ-4/SM as well as older API categories CI-4 Plus, CI-4 and CH-4. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

EcoPower® Heavy Duty Diesel Engine Oils provide maximum protection for longer engine life. EcoPower's robust formulation includes:

- Highest quality re-refined base oils with exceptional purity and lubricating properties that heavy-duty applications demand.
- State-of-the-art performance additives including viscosity index improvers, detergents, dispersants, and anti-wear agents provide maximum protection against breakdown and engine wear
  - Unmatched varnish, sludge and carbon deposit control
  - Low valve train, ring and linear wear
  - Extra protection against bearing and bushing corrosion
  - Boosted oxidation control to minimize oil thickening
  - Excellent high-temperature stability
  - Controls oil thickening and provides good filterability with newer, high soot producing, emission-controlled engines
- EcoPower Engine Oil is beneficial for the environment:
  - Conserves valuable, non-renewable resources
  - Takes up to 85% less energy to produce than oils made from crude according to recent
    Dept. of Energy study
  - Reduces greenhouse gas emissions by over 80%

TYPICAL PROPERTIES		
ECOPOWER®	SAE	10W-30
API Service		CJ-4/SM
Kinematic Viscosity cSt @ 40°C cSt @ 100°C		81.8 12.2
Viscosity Index		146
CCS Viscosity cP @ -25°C		6600
Flash Point, °C		222
Pour Point, °C		-33
Specific Gravity 15.6°C (60°F)		0.868
Color (ASTM)		4.5
TBN		9.5
Sulfated Ash, wt <sup>%</sup>		0.98

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYMHB